

CHAMBER VACUUM PACKERS TOP CAM500T

SKU: CAM500T



ADDITIONAL INFORMATION

Power Kw	<u>1,1 kW (1,5 HP)</u>
power supply	<u>230V/1N/50-60 Hz</u>
Sealing bar	<u>500 mm</u>
Vacuum pump	<u>20 m³/h</u>
Max. vacuum obtainable	<u>98%</u>
Useful chamber dimensions	<u>520 x 520 x 220(h) mm</u>
Machine dimensions (l x l x h mm)	<u>610 x 630 x 500(h) mm</u>
net weight (kg)	<u>72</u>
gross weight (Kg)	<u>79</u>
packaging dimensions (l x l x h mm)	<u>700 x 700 x 720(h) mm</u>
packaging volume (m3)	<u>0.353</u>

Machine aimed at prolonging food preservation times, keeping intact the organoleptic characteristics and preventing the proliferation of bacteria at low temperatures. Stainless steel AISI 304 casing and internal bowl - bowl with rounded corners - plexiglass lid - automatic lid opening at the end of the cycle - LCD control panel with 20 storable programs - oil cleaning function in the pump and soft air function standard included. - piston sealing system with removable sealing bar without cables - provision for inert gas injection - BUSH pump (made in Germany) - "step vac" and "extra vacuum" functions included. Countertop models



