

Pop


Color your business

Friulinox



Pop
by
Friulinox






Fresh or frozen

Temperature range:
+2°C | +10°C
-20°C | -10°C



Easy to use

Control interface with capacitive remote thermostat, simple and intuitive. HACCP alarms indication



100% Recyclable

Exterior made of steel or with skinplate treatment. Moulded polymer interior




Ideal for every installation

Tropicalised refrigeration unit (class "T" 43)




Shiny cleanliness

Very easy to clean and sanitise thanks to the rails moulded directly in the inner side panels



High insulation thickness

Less heat dispersion for less consumption



Multicolor

Unit available in 3 different colours - Black, Red and Stainless Steel to customer and characterise your location



Respect for the environment

Climate class 5 with ecological refrigerant R290

The cold storage specialists have developed a **new range of 700 l cabinets. Pop by Friulinox for conservation.** Multicolor: **black, red or stainless steel**, specific for the Delicatessen and Catering sector. Thanks to the different colours, they can blend in perfectly with exposed furnishings. Available in the **BT negative temperature versions for the conservation of frozen products** or **TN positive temperature versions for the conservation of refrigerated products**, they can accommodate 1/1 GN or 2/1 GN trays.



Features

- Monocoque construction.
- Steel external bottom, internal bottom moulded for containment.
- 80 mm ecological high-density WBS insulation.
- Cataphoresis-coated copper-aluminium evaporating coil.
- Painted condensing coil with high thermal efficiency, requires no cleaning.
- Openable instrument panel to facilitate periodic maintenance.
- Magnetic gasket on all four sides of the door and main body.
- Adjustable high-strength polymer feet H 120±160 mm.

- Automatic condensate evaporation and defrost device without the use of electricity.
- Climate class 5.
- Ecological refrigerant R290.
- Polymer interior with moulded side panels with 24 positions.

Standard accessories

- 3 GN 2/1 steel racks with food-grade coating.

Accessories

- 2 wheel kit with brake.

Model	Colour	Dimensions (L x D x H mm)	Grille capacity	Range Temperature	Refrigerant gas	Power (W)	Absorption (A)	Power supply (V/Ph/Hz)**
CRNO071A-R	Red	700 x 840 x 2090	24 x GN 2/1	+2/+10 °C	R290	132	0,6	220-240/1N~/50
CRNO071A-B	Black	700 x 840 x 2090	24 x GN 2/1	+2/+10 °C	R290	132	0,6	220-240/1N~/50
CRNO071A-X	Stainless steel	700 x 840 x 2090	24 x GN 2/1	+2/+10 °C	R290	132	0,6	220-240/1N~/50
CFNO071A-R	Red	700 x 840 x 2090	24 x GN 2/1	-20/-10 °C	R290	586	2,8	220-240/1N~/50
CFNO071A-B	Black	700 x 840 x 2090	24 x GN 2/1	-20/-10 °C	R290	586	2,8	220-240/1N~/50
CFNO071A-X	Stainless steel	700 x 840 x 2090	24 x GN 2/1	-20/-10 °C	R290	586	2,8	220-240/1N~/50

** Special voltages and frequencies on request

Pop

RF54L00089

FRIULINOX – ALI GROUP Srl a Socio Unico
Via Treviso 4 – 33083 Taiedo di Chions (PN) ITALY
Tel. +39 0434 635411 – Fax +39 0434 635414

info@friulinox.com | www.friulinox.com

See the full range at: www.friulinox.com
The data and information may change based on the continual development of products.

an Ali Group Company



The Spirit of Excellence